



# PRODUCT CATALOG

Professional Equipment for Automotive and Industry

[www.xton.eu](http://www.xton.eu)

# TABLE OF CONTENTS

|                                                     |                                                                      |    |
|-----------------------------------------------------|----------------------------------------------------------------------|----|
| <b>XTON®</b>                                        | ABOUT US                                                             | 3  |
|                                                     | EUROPEAN MANUFACTURER OF<br>EQUIPMENT FOR INDUSTRY AND<br>AUTOMOTIVE | 4  |
|                                                     | ALL INCLUSIVE RENT                                                   | 5  |
|                                                     | XPOWER™ CHEMISTRY                                                    | 6  |
| <b>HOW TO CHOOSE THE RIGHT<br/>WORKSHOP WASHER?</b> |                                                                      | 7  |
| <b>MASTER CLEANER™ SERIES</b>                       | DISCOVER THE MASTER CLEANER™ SERIES                                  | 9  |
|                                                     | ABOUT THE MASTER CLEANER™ SERIES                                     | 10 |
|                                                     | JET CLEANER™ DEVICE                                                  | 10 |
|                                                     | TECHNICAL SPECIFICATIONS – MASTER<br>CLEANER™ & JET CLEANER™ SERIES  | 12 |
| <b>SMART CLEANER™ SERIES</b>                        | DISCOVER THE SMART CLEANER™ SERIES                                   | 14 |
|                                                     | ABOUT THE SMART CLEANER™ SERIES                                      | 15 |
|                                                     | TECHNICAL SPECIFICATIONS – SMART<br>CLEANER™ SERIES                  | 16 |
| <b>FLOW CLEANER™ SERIES</b>                         | DISCOVER THE FLOW CLEANER™ SERIES                                    | 17 |
|                                                     | ABOUT THE FLOW CLEANER™ SERIES                                       | 19 |
|                                                     | TECHNICAL SPECIFICATIONS –<br>FLOW CLEANER™ SERIES                   | 20 |
| <b>DPF BUSINESS</b>                                 |                                                                      | 21 |
| <b>DPF MASTER FLASH™ SERIES</b>                     | DISCOVER THE DPF MASTER<br>FLASH™ SERIES                             | 22 |
|                                                     | ABOUT THE DPF MASTER FLASH™ SERIES                                   | 24 |
|                                                     | DPF HEATER PRO PLUS™                                                 | 25 |
|                                                     | TECHNICAL SPECIFICATIONS –<br>DPF MASTER FLASH™ SERIES               | 26 |
| <b>SANDBLASTING SYSTEMS</b>                         | AQUABLASTER™ (WET SANDBLASTING SYSTEM)                               | 29 |
|                                                     | SANDBLASTER™ (DRY SANDBLASTING SYSTEM)                               | 29 |
|                                                     | TECHNICAL SPECIFICATIONS                                             | 30 |
| <b>MASTER BOX SETS</b>                              |                                                                      | 31 |
| <b>COOPERATE WITH US</b>                            |                                                                      | 35 |



## About Us

We specialize in the design and manufacturing of top-tier equipment for the industrial and automotive sectors. Our foundation is Polish production combined with European quality, confirmed by ISO 9001 and ISO 14001 management systems.

By combining years of experience with strong expertise in automation, electrical engineering, and mechanical design, we create innovative machines that meet the highest safety standards. Continuous investment in modern production facilities ensures the reliability of our solutions.

We offer both serial production and fully customized machines. Our in-house testing facilities significantly shorten the design and R&D process, enabling efficient implementation of new projects.

Our history began with specialized machines for regenerating DPF/FAP/GPF/SCR/CAT filters, which remain our flagship solution to this day. The next milestone was the introduction of high-pressure washers, which quickly became bestsellers. Today, our portfolio continues to expand and includes automatic washers, solvent washers, and sandblasting systems.

XTON devices are used in passenger and heavy-duty vehicle service centers, regeneration facilities, vehicle inspection stations, manufacturing plants, maintenance departments, power plants, mines, and research institutes.

We invite you to cooperate with us.

A handwritten signature in black ink, appearing to read "Tomasz Baciąg".

CEO

XTON sp. z o. o.

# European manufacturer of equipment for industry and automotive



Design and manufacturing of professional  
cleaning equipment



Technical service of equipment



Production of specialized chemicals



Technical and chemical consulting

## Our devices are used worldwide



- United Kingdom
- Northern Ireland
- Germany
- Spain
- France
- Australia
- Estonia


- Romania
- Italy
- Slovakia
- Sweden
- Czech Republic
- Belgium
- Hungary

# One fee – everything included.

As the only manufacturer on the market, we offer a long-term rental model that ensures full technical reliability of the equipment throughout the contract period, along with flexible exit options.

- ✓ **FIXED MONTHLY FEE**
- ✓ **OPTION TO PURCHASE OR RETURN THE DEVICE AT ANY TIME**
- ✓ **REGULAR DELIVERY OF CONSUMABLES**
- ✓ **FULL MANUFACTURER'S WARRANTY FOR THE ENTIRE CONTRACT DURATION**
- ✓ **TECHNICAL SUPPORT AND SPARE PARTS AVAILABLE WITHIN 48 HOURS**



|                                        |  | <b>Leasing</b>                     |
|----------------------------------------|-------------------------------------------------------------------------------------|------------------------------------|
| <b>Contract duration</b>               | 24–48 months                                                                        | 24–60 months                       |
| <b>Fixed Monthly Payment Guarantee</b> | ✓                                                                                   | ✗                                  |
| <b>Manufacturer's Warranty</b>         | For the entire contract period                                                      | 12 months with an option to extend |
| <b>Option to Return the Device</b>     | ✓                                                                                   | ✗                                  |
| <b>Regular Supply of Consumables</b>   | ✓                                                                                   | ✗                                  |
| <b>Option to Purchase the Device</b>   | ✓                                                                                   | ✗                                  |
| <b>Early Buyout Option</b>             | ✓                                                                                   | ✗                                  |
| <b>Dedicated Technical Support</b>     | ✓                                                                                   | ✗                                  |
| <b>Free Device Delivery</b>            | ✓                                                                                   | ✗                                  |

# POWER™

## Chemistry



XPOWER™ chemistry is a comprehensive range of products divided into two specialized lines: for workshops and for industry. Carefully developed formulas ensure high efficiency while protecting cleaned surfaces and minimizing environmental impact.

Our offer includes professional chemical solutions developed individually for each XTON® device. The use of the original XPOWER™ line guarantees maximum process efficiency. These products are presented in the consumables section, included with each device in the following pages of the catalog.

The range includes, among others, the XPOWER™ Industrial line, designed for the most demanding applications. It features specialized Heavy Solvent for cleaning electrical and mechanical equipment, high-

performance Surface Cleaner for industrial surfaces, powerful Hand Cleaner gel, and absorbent mats. These solutions are engineered to deliver maximum efficiency in demanding working environments.

The workshop line includes products such as Brake Degreaser for effective brake cleaning, Steel Cleaner for professional stainless steel maintenance, and Glass Cleaner for glass surfaces and windows. A wide range of products supports daily service operations and enables comprehensive workshop maintenance.

**CONTACT OUR SALES TEAM**

# How to choose the right workshop washer?

Choosing the right workshop washer is a strategic decision that directly impacts service quality, operational efficiency, and overall running costs. Modern cleaning technologies significantly enhance productivity and customer service standards; however, selecting a solution tailored to the specific needs of your business is essential.

## Key criteria for choosing a workshop washer

### What is the size and type of components you will be cleaning?

When selecting a washer, it is important to consider the dimensions, material, and construction of the parts. These factors determine the appropriate cleaning technology, working chamber size, and machine parameters.

### Which standards should the equipment meet?

Operations in service centers and production facilities should be based on recognized management systems. To meet these requirements, professional cleaning technologies must comply with ISO 9001 and ISO 14001 standards.

### What are the costs of purchasing or renting and operating the device?

When analyzing costs, it is important to consider not only the price of the equipment itself, but also water consumption, detergents, energy usage, and potential service costs.


### What is the environmental impact of the selected washer?

Employee safety and comfort are crucial. It is advisable to choose a washer that minimizes harmful emissions and noise levels. It is also important to ensure the machine is equipped with appropriate ventilation and filtration systems.

### What about operation, maintenance, and service support?

Before making a decision, carefully evaluate available training, service requirements, warranty period, and access to technical support and spare parts.

## Quick washer selection guide




### PRESSURE WASHERS

High precision / high cleaning power / heavy contamination



### AUTOMATIC BASKET WASHERS

Serial cleaning / repeatability / large volumes of parts



### MANUAL TABLE WASHERS

Pre-cleaning / tool cleaning / budget solution



## Designed for Professionals

Recommended by:

*Krzysztof Garczyński*

**EKG**



**MASTER  
CLEANER** <sup>TM</sup>  
by **XTON**



# Master Cleaner<sup>TM</sup> Series

Pressure washers



# Discover the Master Cleaner™ Series



**Master Cleaner™ MC850**



**Master Cleaner™ MC1000**



**Master Cleaner™ MC1500**



**Master Cleaner™ MC2000**

# About the Master Cleaner™ Series

The Master Cleaner™ series consists of high-pressure cabinet washers made entirely of stainless steel and high-quality components. High cleaning efficiency and precision are ensured by specialized interchangeable nozzles:

- a rotary nozzle, ideal for removing heavy contamination even from large surfaces,
- a reverse-flow nozzle for intake manifolds, designed for removing carbon deposits from narrow intake channels,
- a nozzle for oil channels with a diameter of just 8 mm, enabling precise cleaning and unclogging of narrow engine passages.

The washers operate in a closed-loop system with liquid temperatures of up to 50°C and are equipped with a high-pressure system featuring adjustable liquid flow in the range of 6–12 L/min, allowing effective removal of grease, oil, carbon deposits, metal shavings, and contaminants generated during machining processes. The dual liquid filtration system and integrated oil separator increase process efficiency and extend the lifespan of the working medium. A pneumatically lifted lid, adjustable feet, and an air blow-off system for the window ensure comfortable operation.

The series includes models with varying worktop widths and tank capacities, allowing the device to be tailored to the size of the cleaned components. Master Cleaner™ enables precise cleaning of engine parts, effectively removing carbon deposits from intake manifolds, EGR valves, and other components exposed to heavy contamination. The washer is suitable for cleaning both smaller components in automotive workshops and larger parts, for example in maintenance departments.



**Jet Cleaner™ JC1000**

## Jet Cleaner™ Device

Hybrid high-pressure washer

Jet Cleaner™ JC1000 is a specialized version of a high-pressure washer. Its key advantage is an external high-pressure lance (up to 140 bar) with a 25-meter hose. It enables efficient cleaning of large components that do not fit inside the chamber, as well as workshop surfaces contaminated with oil or mud. Thanks to its cabinet-based design (derived from the Master Cleaner™ series), it can also operate inside the chamber. A mode switch allows safe switching between internal and external use. The lance can be supplied either from the network or directly from the tank.

## Equipment:

- liquid level and temperature sensors,
- dual liquid filtration system,
- heated cleaning solution,
- compressed air gun up to 8 bar,
- high-pressure nozzle with adjustable flow rate (6–12 l/min),
- low-pressure brush up to 5 l/min,
- LED lighting,
- pneumatic chamber opening system,
- adjustable feet (100 mm range),
- dual foot switch,
- air blow-off for viewing window,
- oil separator,
- XPOWER™ Active Cleaner 10 L – starter pack,
- external high-pressure lance with 25 m hose\*.

\*Available for Jet Cleaner™

## Optional equipment:

- rigid spray arm,
- manual rotary table,
- rotary nozzle,
- intake manifold cleaning nozzle,
- oil channel cleaning nozzle,
- thermally insulated tank,
- stand with holder for external lance and hose\*\*.

## Accessories and Consumables:



Intake manifold cleaning  
nozzle



Oil channel cleaning  
nozzle



Rotary nozzle



String filter cartridge



Gloves



Flow-through brush



XPOWER™ Active Cleaner



XPOWER™ Active Cleaner  
PLUS

# Technical Specifications – Master Cleaner™ & Jet Cleaner™ Series



| Master/Jet Cleaner™                                       | Master Cleaner™<br>MC850                            | Master Cleaner™<br>MC1000                            |
|-----------------------------------------------------------|-----------------------------------------------------|------------------------------------------------------|
| <b>Weight</b>                                             | 200 kg                                              | 225 kg                                               |
| <b>External Dimensions</b><br>(Open Chamber: W × D × H)   | 110 × 78 × 245 cm                                   | 125 × 78 × 245 cm                                    |
| <b>External Dimensions</b><br>(Closed Chamber: W × D × H) | 110 × 78 × 178 cm                                   | 125 × 78 × 178 cm                                    |
| <b>Internal Chamber Dimensions</b>                        | 80 × 70 × 64 cm                                     | 95 × 70 × 64 cm                                      |
| <b>Heated Liquid Tank</b>                                 | 90 L / 65 L<br><i>up to the oil separator level</i> | 120 L / 85 L<br><i>up to the oil separator level</i> |
| <b>Operating Temperature</b>                              | up to 50°C                                          | up to 50°C                                           |
| <b>Maximum Power</b>                                      | 7,5 kW                                              | 7,5 kW                                               |
| <b>Power Supply</b>                                       | 3 × 400V                                            | 3 × 400V                                             |
| <b>Pneumatic Supply</b>                                   | 6–8 bar                                             | 6–8 bar                                              |
| <b>Pump Operating Pressure</b>                            | 140 bar                                             | 140 bar                                              |
| <b>Dual Liquid Filtration System</b>                      | yes                                                 | yes                                                  |
| <b>High-Pressure Lance Flow Rate</b>                      | up to 12 L/min                                      | up to 12 L/min                                       |
| <b>Manual Washing Flow Rate</b><br>(Flow-Through Brush)   | up to 5 L/min                                       | up to 5 L/min                                        |
| <b>Dual Foot Switch</b>                                   | yes                                                 | yes                                                  |
| <b>Oil Separator</b>                                      | yes                                                 | yes                                                  |
| <b>External High-Pressure Lance</b>                       | no                                                  | no                                                   |
| <b>All INCLUSIVE™ Rent</b>                                | ✗                                                   | ✓                                                    |
| <b>Comfort Pack</b>                                       | ✓                                                   | ✓                                                    |


**Master Cleaner™  
MC1500**
**Master Cleaner™  
MC2000**
**Jet Cleaner™  
JC1000**

230 kg

250 kg

230 kg

175 × 78 × 245 cm

225 × 78 × 245 cm

125 × 78 × 245 cm

175 × 78 × 178 cm

225 × 78 × 178 cm

125 × 78 × 178 cm

145 × 70 × 64 cm

195 × 70 × 64 cm

95 × 70 × 64 cm

215 L / 160 L  
*up to the oil separator level*

285 L / 200 L  
*up to the oil separator level*

120 L / 85 L  
*up to the oil separator level*

up to 50°C

up to 50°C

up to 50°C

7,5 kW

7,5 kW

7,5 kW

3 × 400V

3 × 400V

3 × 400V

6–8 bar

6–8 bar

6–8 bar

140 bar

140 bar

140 bar

yes

yes

yes

up to 12 L/min

up to 12 L/min

up to 12 L/min

up to 5 L/min

up to 5 L/min

up to 5 L/min

yes

yes

yes

yes

yes

yes

no

no

no



**SMART**  <sup>TM</sup>  
**CLEANER**  
by **XTON**



# Smart Cleaner<sup>TM</sup>

## Series

Automatic basket washers



# Discover the Smart Cleaner™ Series



**Smart Cleaner™ SC850**



**Smart Cleaner™ SC1000**

## About the Smart Cleaner™ Series

Smart Cleaner™ automatic basket washers are designed for degreasing and cleaning machine parts contaminated with oil or grease. This is an ideal solution for workshops, production plants, and service facilities requiring fast and efficient cleaning of large components. The machines feature:

- a rotating basket for parts,
- a heated tank (up to 80°C),
- high-flow spray nozzles (up to 250 L/min).

### Equipment:

- liquid level and temperature sensors,
- dual liquid filtration system,
- rotating basket,
- heated tank,
- adjustable leveling feet,
- disc oil separator,
- touch panel,
- automatic washing programs,
- XPOWER™ Active Cleaner BA 10 L – starter pack

### Consumables:



XPOWER™ Active Cleaner  
BA



Smart Cleaner™ filter bag  
BA

# Technical Specifications – Smart Cleaner™ Series



| Smart Cleaner™                                            | Smart Cleaner™<br><b>SC850</b>                              | Smart Cleaner™<br><b>SC1000</b>                             |
|-----------------------------------------------------------|-------------------------------------------------------------|-------------------------------------------------------------|
| <b>Weight</b>                                             | 185 kg                                                      | 200 kg                                                      |
| <b>External Dimensions</b><br>(Open Chamber: W × D × H)   | 135 × 160 × 194 cm                                          | 160 × 142 × 250 cm                                          |
| <b>External Dimensions</b><br>(Closed Chamber: W × D × H) | 135 × 108 × 141 cm                                          | 160 × 120 × 165 cm                                          |
| <b>Rotating Basket Diameter</b>                           | Ø 85                                                        | Ø 100                                                       |
| <b>Working Space Above the Basket</b>                     | 50 cm                                                       | 60 cm                                                       |
| <b>Rotating Basket Load Capacity</b>                      | 300 kg                                                      | 300 kg                                                      |
| <b>Cycle Time Programming</b>                             | 0 – 240 min                                                 | 0 – 240 min                                                 |
| <b>Tank Capacity</b>                                      | up to 200 L / 200 L<br><i>up to the oil separator level</i> | up to 300 L / 200 L<br><i>up to the oil separator level</i> |
| <b>Power Socket</b>                                       | 32 A                                                        | 32 A                                                        |
| <b>Liquid Temperature</b>                                 | up to 80°C                                                  | up to 80°C                                                  |
| <b>Heater Power</b>                                       | 2 × 4,5 kW                                                  | 2 × 4,5 kW                                                  |
| <b>Spray Pressure</b>                                     | 3 – 4 bar                                                   | 3 – 4 bar                                                   |
| <b>Power Supply</b>                                       | 3 × 400V                                                    | 3 × 400V                                                    |
| <b>Washing Pump Performance</b>                           | up to 250 L/min                                             | up to 250 L/min                                             |
| <b>Safety Features</b>                                    | temperature sensor / emergency<br>stop / limit switch       | temperature sensor / emergency<br>stop / limit switch       |
| <b>All INCLUSIVE™ Rent</b>                                |                                                             |                                                             |
| <b>Comfort Pack</b>                                       |                                                             |                                                             |

\*For SC1200 and SC1500 models, contact your sales representative.

**FLOW  
CLEANER** <sup>TM</sup>  
*by XTON*

ISO  
14001

ISO  
9001

CE

# Flow Cleaner<sup>TM</sup> Series

Manual table washers



# Discover the Flow Cleaner™ Series



**Flow Cleaner™ FC800**



**Flow Cleaner™ FC1200**



**Flow Cleaner Mobile™ FCM2000**



# About the Flow Cleaner™ Series

The Flow Cleaner™ series consists of ergonomic table-top washers designed for cold solvent-based cleaning of components. The machines are equipped with a worktable, lid, and a hose fitted with a low-pressure flow-through brush for precise cleaning, as well as a segmented hose for rinsing off residual contaminants. The devices use petroleum-based cleaning agents that effectively dissolve grease and heavy contamination. They are ideal for cleaning engine parts, hydraulic system components, workshop tools, and elements covered with thick oil or grease.

## Equipment:

- adjustable feet\*,
- flow-through brush,
- segmented hose,
- 5 m power cable with 230v plug,
- LED lighting,
- XPOWER™ Flowwash Solvent 60 L – starter pack.

\*Available for Flow Cleaner™ series devices. The Flow Cleaner Mobile™ FCM2000 is equipped with swivel casters without height adjustment.

## Accessories and consumables:



Flow-through Brush



XPOWER™ Flowwash Solvent



XPOWER™ Flowwash Solvent 60 L

## A washer tailored to your needs

### Do you need a machine with non-standard dimensions?

With our modern production facilities, advanced machinery, and a team of experienced engineers and technologists, we are able to design and deliver high-quality solutions tailored to your specific requirements.

**ASK YOUR SALES REPRESENTATIVE FOR DETAILS**

# Technical Specifications – Flow Cleaner™ Series



| <b>Flow Cleaner™</b>                                                 | <b>Flow Cleaner™<br/>FC800</b> | <b>Flow Cleaner™<br/>FC1200</b>     | <b>Flow Cleaner Mobile™<br/>FCM2000</b> |
|----------------------------------------------------------------------|--------------------------------|-------------------------------------|-----------------------------------------|
| <b>Weight</b>                                                        | 85 kg                          | 100 kg                              | 150 kg                                  |
| <b>External Dimensions</b><br>(Open / Handle Extended:<br>W × D × H) | 85 × 85 × 210 cm               | 125 × 85 × 200 cm                   | 212 × 105 × 96 cm                       |
| <b>External Dimensions</b><br>(Closed / Handle Folded: W<br>× D × H) | 85 × 85 × 130 cm               | 125 × 85 × 130 cm                   | 212 × 105 × 45 cm                       |
| <b>Worktop Dimensions</b>                                            | 75 × 75 cm                     | 115 × 75 cm                         | 65 × 179 cm                             |
| <b>Loading Height</b>                                                | 95 cm                          | 95 cm                               | 32 cm                                   |
| <b>Worktop Load Capacity</b>                                         | up to 300 kg                   | up to 300 kg                        | up to 300 kg                            |
| <b>Tank Capacity</b>                                                 | 60 L                           | 200 / 60 L                          | 100 L                                   |
| <b>Liquid Temperature</b>                                            | –                              | –                                   | –                                       |
| <b>Maximum Power</b>                                                 | 200 W                          | 200 W                               | 100 W                                   |
| <b>Power Supply</b>                                                  | 230 V                          | 230 V                               | 230 V / 50 Hz                           |
| <b>Pump Performance</b>                                              | up to 12 L / min               | up to 12 L / min                    | up to 12–30 L / min                     |
| <b>Safety Features</b>                                               | main power switch              | main power switch                   | main power switch                       |
| <b>All INCLUSIVE™ Rent</b>                                           | <input type="checkbox"/>       | <input checked="" type="checkbox"/> | <input type="checkbox"/>                |
| <b>Comfort Pack</b>                                                  | <input type="checkbox"/>       | <input type="checkbox"/>            | <input type="checkbox"/>                |

\*For custom projects, contact your sales representative.

# DPF Business

## – *is it profitable?*

The automotive market in Europe is undergoing rapid transformation. Increasingly stringent emission standards, the introduction of Clean Transport Zones, and the growing number of vehicles equipped with DPF and GPF filters make particulate filter regeneration one of the most promising workshop services. For service providers, this represents a real opportunity to grow their business and increase revenue with minimal operating costs.

Hydrodynamic technology restores filter efficiency by up to 99%, while the process itself costs only a fraction of the service price. With service rates ranging from €150 to €1,000, completing just three regeneration services is enough to cover the monthly rental instalment. All that is required is a properly equipped workshop space to start a profitable regeneration operation.

### DPF MASTER FLASH™ – a technology that pays off

DPF filter cleaning is based on a hydrodynamic method. The process begins with the introduction of water and air under high pressure, generating turbulent flow – intense, dynamic currents that remove deposits from inside the filter.

Next, thanks to the cavitation effect, which involves the implosion of gas bubbles caused by pressure changes, even deeply embedded contaminants are removed from the micropores. The use of professional chemical agents further enhances the removal of deposits and impurities from the filter.

The final stage is drying at temperatures of up to 130°C, which completely removes moisture and prepares the filter for further use. The entire process begins and ends with a measurement of the filter contamination level. It is important to emphasize that professional regeneration does not affect the filter structure, making it a safe solution.

### What do you need to get started?

#### Facility Requirements

A properly designated workspace of at least 20 m² is essential, allowing for convenient machine placement, filter handling, and organization of intake and dispatch areas. A three-phase power supply (3 × 400 V AC, approx. 12 kW, 32 A 5P), a water connection, and a permanent connection to the sewage system are required. A compressed air source is also necessary – a compressor with a minimum capacity of 300 L/min – as well as an efficient ventilation system ensuring proper air exchange in the room.

#### Financial Requirements

The investment can be carried out through direct purchase of the equipment or by using leasing or financing with an initial contribution. An alternative is a long-term rental model, such as XTON Rent All Inclusive™ with a purchase option and fixed monthly fee.

It is also worth checking the possibility of obtaining funding for equipping a new workstation or grants, for example EU subsidies, which can support the development of a new service.



### Are you planning to start a new business focused on diesel particulate filter regeneration?

Contact us and choose a model from the DPF Master Flash™ series that ensures a fast launch, high service quality, and stable business growth.

WRITE TO US AT [SALES@XTON.EU](mailto:SALES@XTON.EU)

# DPF Master Flash<sup>TM</sup> Series

DPF filter cleaning machines



# Discover the DPF Master Flash™ Series



**DPF Master Flash™  
Standard**



**DPF Master Flash™  
Professional**



**DPF Master Flash™  
Professional PLUS**



**DPF Master Flash™  
DUAL AI**

# About the DPF Master Flash™ Series

The DPF Master Flash™ series is a line of machines designed for the regeneration of particulate filters and catalytic converters. Depending on the model, they are intended for servicing passenger cars, vans, trucks, buses, as well as agricultural and construction machinery.

All models are manufactured from AISI 304 stainless steel and acid-resistant AISI 316 steel, and are built using components from renowned European manufacturers. The machines enable regeneration of DPF, FAP, GPF, SCR, EURO 5 and EURO 6 filters, as well as catalytic converters. Each unit is equipped with a liquid filtration system, precise contamination measurement (backpressure test), and – in higher models – an integrated drying system.

The machines operate in automatic cycles within a closed-loop system and use hydrodynamic technology, ensuring regeneration efficiency of up to 99%. They remove residues of PM10 and PM2.5 particles, carbon deposits, oil, cerium, and heavy metals without mechanical interference with the filter monolith.

The series includes solutions ranging from compact and cost-effective models for workshops starting regeneration services to technologically advanced industrial-class machines with high pump performance, increased tank capacity, and advanced automation systems. DPF Master Flash™ is a professional solution for workshops, regeneration centers, and companies operating large vehicle fleets.

## Equipment:

- DPF filter contamination measurement system,
- integrated filter drying system up to 130°C,
- multi-stage filtration system,
- integrated thermal printer for filter parameter reports,
- Ethernet controller for remote diagnostics,
- adapter set for all filter types
- touch control interface,
- starter consumables kit,
- mobile application enabling remote control of the device from anywhere in the world.

## Optional accessories:

- automatic bidirectional filter cleaning\*,
- second liquid circuit with an additional pump,
- thermal insulation of the liquid tank,
- automatic liquid level refill,
- Quick-X filter mounting system,
- endoscopic camera,
- euro 5 filter adapters, euro 6 adapter\*\*,
- automatic detergent dosing.

\*Standard equipment for DPF Master Flash™ Professional DUAL AI and EXPERT models.

\*\*Standard equipment for DPF Master Flash™ Professional PLUS and EXPERT models.

**All devices and accessories  
can be found in our store:  
[www.xton24.eu](http://www.xton24.eu)**

**FREE DELIVERY FROM EUR 300 NET**





# DPF Heater PRO PLUS™ Device

A device designed for drying all types of particulate filters and catalytic converters, made entirely of stainless steel. It features an integrated measurement system and enables drying at temperatures of up to 130°C using a side-channel blower. The built-in thermal printer allows printing of filter contamination measurement results.

The device is an ideal additional option for particulate filter cleaning machines that do not have an integrated drying system\*.

It can also serve as an excellent complement to machines equipped with a drying system by doubling the processing capacity of the regeneration process.

*\*\*The device can be purchased as a set with the DPF Master Flash™ Standard machine. Ask your sales representative for details.*

## DPF Heater PRO PLUS™

## Accessories and consumables for the DPF Master Flash™ series:



Filter cartridge



Filter bag



XPOWER™ DPF Cleaner



XPOWER™ DPF Cleaner  
PLUS



Air/water hose



QuickX mounting system



EURO 6 adapter



Angle adapter

# Technical Specifications – DPF Master Flash™ series



|                                        | DPF Master Flash™<br><b>Standard</b>                  | DPF Master Flash™<br><b>Professional</b>                                  |
|----------------------------------------|-------------------------------------------------------|---------------------------------------------------------------------------|
| <b>Supported Vehicles</b>              |                                                       |                                                                           |
| <b>Weight (W × D × H)</b>              | 150 kg                                                | 600 kg                                                                    |
| <b>External Dimensions (W × D × H)</b> | 180 × 80 × 135 cm                                     | 210 × 95 × 215 cm                                                         |
| <b>Chamber Dimensions (W × D × H)</b>  | –                                                     | 140 × 69 × 107 cm                                                         |
| <b>Tank Capacity</b>                   | 100 L                                                 | up to 185 L                                                               |
| <b>Operating Pressure</b>              | 3 bar                                                 | 6–8 bar                                                                   |
| <b>Maximum Power</b>                   | 7 kW                                                  | 12 kW                                                                     |
| <b>Power Supply</b>                    | 3 × 400V                                              | 3 × 400V                                                                  |
| <b>Closed Chamber</b>                  | no                                                    | yes                                                                       |
| <b>Liquid Temperature</b>              | adjustable 30°C – 70°C                                | adjustable 30°C – 70°C                                                    |
| <b>Filtration Pump Performance</b>     | up to 133 L/min                                       | up to 133 L/min                                                           |
| <b>Bidirectional Regeneration Mode</b> | no                                                    | optional                                                                  |
| <b>Dual Liquid Circuits</b>            | no                                                    | no                                                                        |
| <b>Air Connection</b>                  | quick coupling DN7.2                                  | quick coupling DN7.2                                                      |
| <b>Operating Noise Level</b>           | < 70 dB                                               | < 70 dB                                                                   |
| <b>Liquid Filtration</b>               | 2-stage, 5–100 mikrons                                | 3-stage, 5–100 mikrons                                                    |
| <b>Air Flow</b>                        | no                                                    | up to 390 m³                                                              |
| <b>Measurement Printout</b>            | no                                                    | thermal printer                                                           |
| <b>Safety Features</b>                 | level sensor / temperature sensor /<br>emergency stop | temperature sensor / pressure<br>sensor / door sensor / emergency<br>stop |
| <b>All INCLUSIVE™ Rent</b>             | <input checked="" type="checkbox"/>                   | <input checked="" type="checkbox"/>                                       |
| <b>Comfort Pack</b>                    | <input checked="" type="checkbox"/>                   | <input checked="" type="checkbox"/>                                       |


**DPF Master Flash™  
Professional PLUS**


650 kg

210 × 115 × 215 cm

140 × 89 × 107 cm

up to 275 L

6–8 bar

12kW

3 × 400V

yes

adjustable 30°C – 70°C

up to 250 L/min

optional

no

quick coupling DN7.2

&lt; 70 dB

3-stage, 5–100 mikrons

up to 430 m³

thermal printer

temperature sensor / pressure  
sensor / door sensor / emergency  
stop

**DPF Master Flash™  
DUAL AI**


720 kg

210 × 125 × 215 cm

140 × 89 × 107 cm

up to 275 L

7–8 bar

12kW

3 × 400V

yes

adjustable 30°C – 70°C

up to 250 L/min

yes

no

quick coupling DN7.2

&lt; 70 dB

4-stage, 5–20 mikrons

up to 430 m³

thermal printer

temperature sensor / pressure  
sensor / door sensor / emergency  
stop

**DPF Master Flash™  
Expert**


950 kg

270 × 145 × 215 cm

200 × 105 × 107 cm

up to 600 L

7–8 bar

18 kW

3 × 400V

yes

adjustable 30°C – 70°C

up to 450 L/min

yes

yes

quick coupling DN7.2

&lt; 70 dB

4-stage, 5–100 mikrons

up to 1060 m³

thermal printer

temperature sensor / pressure  
sensor / door sensor / emergency  
stop


**AQUA  
BLASTER**™  
by **XTON**

**SAND  
BLASTER**™  
by **XTON**



# Sandblasting systems **Aquablasters™** **Sandblasters™**



NEW!

**Aquablaster™**

# Aquablaster™

## Wet sandblasting system

The wet sandblasting system operates in a closed-loop configuration, utilizing a dual-pump system and compressed air.

The main mixing-pressure pump, made of abrasion-resistant materials, is responsible for delivering the abrasive-liquid mixture to the lance equipped with a working gun. The circulation pump distributes the cleaned liquid, ensuring effective removal of residual working medium from the processed components, as well as contaminants from the viewing window.

Wet abrasive blasting technology enables a smooth and aesthetically refined surface finish without the risk of material damage and without generating harmful dust. Aquablaster™ is ideally suited for the regeneration and restoration of delicate surfaces made of materials such as aluminum or brass. The specially designed gun, combined with a wide pressure adjustment range, also allows effective removal of heavy contamination from steel and cast iron components.

**Sandblaster INOX™**

# Sandblaster™

## Dry sandblasting system

A compact stainless steel sandblaster designed for precise cleaning and effective removal of corrosion from metal components.

The device operates in a closed-loop system and is equipped with an integrated dust extractor and filtration system, ensuring a clean workspace and safe working conditions. The 250 L chamber allows for convenient processing of various parts, while quiet operation and high-quality, durable gloves ensure user comfort even in compact workshop spaces.

# Technical Specifications



| Sandblasting systems      | Wet sandblasting system<br><b>Aquablaster™</b>                                                                                                                          | Dry sandblasting system<br><b>Sandblaster™ (INOX)</b> |
|---------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------|
| Weight                    | 320 kg                                                                                                                                                                  | 180 kg                                                |
| External Dimensions       | 130 × 120 × 195 cm                                                                                                                                                      | 95 × 75 × 185 cm                                      |
| Chamber Size              | 105 × 90 × 70 cm                                                                                                                                                        | 88 × 70 × 60 cm                                       |
| Chamber Capacity          | 500 L                                                                                                                                                                   | 250 L                                                 |
| Power Supply Voltage      | 400 V / 50 Hz                                                                                                                                                           | 230 V / 50 Hz                                         |
| Operating Pressure        | up to 5 bar                                                                                                                                                             | up to 10 bar                                          |
| Cleaning Efficiency       | up to 5 m³/h                                                                                                                                                            | up to 12 m³/h                                         |
| Cleaning Grade            | –                                                                                                                                                                       | Sa 3 (ISO 8501-1)                                     |
| Air Consumption           | 500 L/min (for 3 mm nozzle)                                                                                                                                             | 2000 L/min (for 6 mm nozzle)                          |
| Maximum Air Flow          | 2000 L/min                                                                                                                                                              | up to 10500 L/min                                     |
| Supported Nozzle Sizes    | 4–14 mm                                                                                                                                                                 | 2–10 mm                                               |
| Nozzle Material           | stainless steel / ceramic                                                                                                                                               | tungsten carbide                                      |
| Abrasive Valve            | –                                                                                                                                                                       | MIKRO II                                              |
| Viewing Window Dimensions | 270 × 780 mm                                                                                                                                                            | 270 × 510 mm                                          |
| Worktable Load Capacity   | up to 150 kg                                                                                                                                                            | up to 200 kg                                          |
| Operating Temperature     | 10 – 50°C                                                                                                                                                               | 10 – 50°C                                             |
| Mixing-Pressure Pump      | 2,2 kW, flow rate 20–40 L/min                                                                                                                                           | –                                                     |
| Construction              | stainless steel, thickness 1.5–2 mm                                                                                                                                     | stainless steel                                       |
| Equipment                 | windscreen wiper and washing system, pressure reducer, gloves, LED lighting                                                                                             | LED lighting, high-quality gloves                     |
| Optional Accessories      | additional filtration system, external loading table, touchscreen display, VS gun, rotating basket, pass-through door for cleaning long components, manual rotary table | rotating basket, rotary table                         |

**All INCLUSIVE™ Rent**



**MASTER  
BOX**



# Master Box Sets

Professional technological infrastructure designed to meet the needs of the modern automotive and industrial sectors





**DPF Master Flash™ Professional PLUS + Master Cleaner™ MC1000**

## Master Box\*

### DPF Master Flash™ Professional PLUS + Master Cleaner™ MC1000

The set includes a machine for cleaning DPF, GPF, FAP, SCR, EURO 5 and EURO 6 filters, along with a high-pressure cabinet washer for cleaning components such as engine parts and intake systems.

This solution is designed for automotive workshops, truck and bus service centers, component regeneration facilities, as well as industrial companies and maintenance departments. The equipment ensures full control over the cleaning and regeneration process, enables independence from subcontractors, and helps minimize vehicle fleet downtime.

*\*The set is also available with the DPF Master Flash™ DUAL AI*



**DPF Master Flash™ Professional PLUS + Smart Cleaner™ SC1000**

## Master Box\*

### DPF Master Flash™ Professional PLUS + Smart Cleaner™ SC1000

The set includes a machine for cleaning DPF, GPF, FAP, SCR, EURO 5 and EURO 6 filters, along with an automatic basket washer designed for cleaning complex-shaped components or multiple parts in a single cycle.

The set includes a machine for cleaning DPF, GPF, FAP, SCR, EURO 5 and EURO 6 filters, along with an automatic basket washer designed for cleaning complex-shaped components or multiple parts in a single cycle.

*\*\*The set is also available with the DPF Master Flash™ DUAL AI*



**Master Cleaner™ MC1000 +  
Smart Cleaner™ SC1000 +  
Flow Cleaner™ FC1200**

# Master Box

## Master Cleaner™ MC1000 + Smart Cleaner™ SC1000 + Flow Cleaner™ FC1200

A professional set of three washers – automatic, high-pressure, and solvent-based – ensures a complete cleaning process for components, from intensive degreasing to precise final cleaning and maintenance.

This solution performs equally well in single, precision service operations and in serial production processes. A comprehensive cleaning equipment setup allows you to organize cleaning processes in line with technical cleanliness requirements, while maximizing efficiency and repeatability with full control over every stage of the process.



**Master Cleaner™ MC1000 +  
Smart Cleaner™ SC1000 +  
Aquablaster™**

# Master Box

## Master Cleaner™ MC1000 + Smart Cleaner™ SC1000 + Aquablaster™

A professional set of three cleaning technologies – high-pressure, automatic, and wet abrasive blasting – provides a complete solution for modern automotive workshops.

The synergy of these systems enables a full range of processes: from serial cleaning of engine components in a basket, through precise cleaning of oil channels and intake manifolds under high pressure, to dust-free restoration of aluminum parts using the Aqua-Blast method. With this setup, the workshop gains full technological independence, allowing efficient preparation of components for assembly and reducing vehicle downtime at the service station.



**DPF Master Flash™ Professional PLUS + Sandblaster™**

# Master Box\*

## DPF Master Flash™ Professional PLUS + Sandblaster™

The set includes a machine for cleaning DPF, GPF, FAP, SCR, EURO 5 and EURO 6 filters, along with a pressure sandblaster designed for surface cleaning and corrosion removal. The set enables you to provide comprehensive services to your customers – from filter regeneration to sandblasting and glass bead blasting of components. The equipment is ideal for automotive workshops, regeneration centers, and companies specializing in component refurbishment.

*\*The set is also available with the DPF Master Flash™ DUAL AI*

**NEW!**



**DPF Master Flash™ Professional PLUS + Aquablaster™**

# Master Box\*

## DPF Master Flash™ Professional PLUS + Aquablaster™

The set includes a machine for cleaning DPF, GPF, FAP, SCR, EURO 5 and EURO 6 filters, along with a wet sandblasting system designed for dust-free abrasive processing of components.

This is an ideal combination for workshops, regeneration centers, and industrial companies that require effective particulate filter regeneration and a solution that delivers a smooth, clean, and high-quality surface finish.

*\*The set is also available with the DPF Master Flash™ DUAL AI*

# Become Our Partner

Join our partner network and actively promote and sell XTON® products and services designed for automotive workshops and industrial companies. Build a strong brand image with a company that delivers proven and valued solutions.

## Do you run a workshop abroad?

### Become our Partner!

We cooperate with professionals across Europe who run automotive workshops or have experience in the automotive industry. Become our representative in your region, promote and sell XTON equipment. Open up new business opportunities and increase your revenue with the full support and reputation of a recognized Polish brand.



Please send us an email with the subject "XTON Partner Program" to [sales@xton.eu](mailto:sales@xton.eu)



## Do you own an XTON® device?

Do you know someone who runs an automotive workshop or a company where technical cleanliness is essential and is looking for proven equipment? Recommend our machines by sharing your positive experience. If your referral directly leads to the sale or rental of our equipment, you will receive an attractive commission from us!

### Share your opinion online

- Write a review on our Google Business Profile. You can also add a photo of our machine operating in your company.



Leave us a review on Google!

- Post a photo or video featuring your XTON machine on Facebook, Instagram, TikTok or YouTube. Tag our profile and add #xton.

## What do you gain by partnering with XTON®?



High commission



Simple agreement



Unlimited earning potential



No intermediaries

# Trusted by



## **XTON®**

### COMPANY INFORMATION

XTON sp. z o. o.  
ul. Stanisława Wigury 14  
33-300 Nowy Sącz  
POLAND

VAT EU: PL7343606177  
REGON: 180202681  
KRS: 0000122264

### CONTACT

Office: + 48 18 479 16 01

Sales Department:

 + 48 18 479 16 10

 + 48 18 479 16 11

Service: + 48 18 479 16 31